

DAS-4 Eco



External memory extension for DMS 80/160/240

Description

- The newly developed DAS 4 Eco offers cost-effective storage expansion for the DMS 80/160 and 240 in keeping with the overall concept. The housing of the device, which is only one U high, can contain max. 4 SATA hard disks in lockable slide-in units with a maximum total capacity of 2 TB.
- The hard disks can be replaced from the front of the recorder and in case of a hard disk failure the „EasyChange“ function ensures greatest ease of maintenance. Two redundant high performance fans guarantee optimal ventilation of the storage unit. Power is supplied directly via the 12V output of the DMS 80/160/240 - an additional power supply unit is therefore not necessary.

Features

- 4 lockable slots for Dallmeier approved and authorised SATA hard disks
- Easy Change functionality for hard disk breakdown (no hot-plug, no hot-swap)
- 2 redundant high performance fans for optimal ventilation
- Direct power supply via DMS 80/DMS 160/DMS 240 (12V output), no additional power supply necessary
- Easy installation (Plug&Play)
- Practice oriented handling

Item number

- 180.400

DAS-4 Eco

Protocol

| | |
|---------------|--------------------------------------|
| Type | SATA2 (x4) MultiLane |
| Protocol | SATA 2 |
| Transfer rate | 300 GB/s |
| Socket | Infiniband (with special assignment) |

Hard disks

| | |
|------------------|------------|
| Quantity | Max. 4 |
| Type | 3.5 " |
| Storage capacity | As ordered |
| Interface | SATA 1/2 |

Options

| | |
|----------------|----------------------|
| Mounting kit 1 | 19" installation kit |
|----------------|----------------------|

Other details

| | |
|--------------------------|---|
| Mains voltage | 12V DC / max. 5A |
| Power consumption | Max. 72 W |
| Dimensions | W 420 x H 44 x D 350 mm (1HU) |
| Temperature | 0 °C - 50 °C (0 °C - 35 °C recommended) |
| Weight | Appr. 6kg (incl. 4 HDD) |
| Approvals/certifications | CE, FCC, ACA |
| Warranty | 24 months |