

DIS-2/M StreamerPro



DIS-2/M StreamerPro

Features

- Stand-alone
- Camera inputs: CVBS (BNC) and S-Video (mini DIN 4)
- Data rate (constant and dynamic): 250 Kbit/sec. - 16 Mbit/sec
- Video(PAL): up to 720x576 at 25 frames/sec.
- Various video and audio standards can be selected freely
- Other inputs/outputs:
 - 1x100 Base T x RJ45
 - 1xRS232/RS485 RJ12
 - 4 input contacts
 - 4 output contacts
 - 1x Audio-IN 3.5mm phone jack
- 12V DC power supply
- Housing dimensions: 45x110x245mm

Item number

- SL002.ENC.001.B

DIS-2/M StreamerPro

Format

Video	MPEG-2 MP@ML (progressive oder interlaced) MPEG-4 ISO/IEC 14496 MJPEG
Audio	MPEG-1 Layer 2 MP3 (planned) G.722 (planned)

Video IN / OUT

Video IN (CVBS)	1 x BNC
Video IN (S-Video)	1 x mini DIN 4
Video OUT	Streaming (LAN)

Audio IN / OUT

Audio IN	1x 3.5 mm phone jack
Audio OUT	Streaming (LAN)

Interfaces

LAN	1 x RJ45, 10/100 Mbit
Contact IN	4 x on 16-pole Weidmüller connection strip, 1 function per contact
Relay OUT	4 x on 16-pole Weidmüller connection strip, configurable as maker or breaker
Serial	1 x RJ12, RS232/RS485
USB	none

Other hardware details

Mains voltage (incl. admissible tolerance)	12V DC
Dimensions	110x45x245
Temperature	+5 °C - 40 °C
Humidity	5 - 70 % (non-condensing)
Weight	2 kg
Languages	German, English, French, Spanish (others on request)