

MicroStream



MicroStreamer

Features

- Analogue video signal, input: CVBS (BNC)
- Various video and audio standards can be selected freely
- IP Board: Dual MIPS risk processor
- Integrated web server, integrated interface for user programs
- Other inputs/outputs:
 - 1xRS485
 - 1x100 Base T x RJ45
- Weight: app. 260g/9.2 oz
- Power supply: 12V DC, 24V AC
- Housing dimensions: 45x45x125mm

Options

- Power pack universal 110-240V on 12V DC

Item number

- 200.434

MicroStreamer

Format

Video	MPEG-2 MPEG-4 MJPEG
Audio	MPEG-1 Layer 2 MP3 (planned) G.722 (planned)

Video IN / OUT

Video IN	1x BNC
Video OUT	Streaming (LAN)
Video OUT (test)	1x 2.5 mm phone jack

Audio IN / OUT

Audio IN	1x 3.5 mm phone jack
Audio OUT	Streaming (LAN)

Interfaces

Serial	1 x on 2-pole Weidmüller connection strip, RS485
Ethernet	1 x RJ45, 10/100 Mbit

Other hardware details

Mains voltage (incl. admissible tolerance)	12V DC, 24V AC
Power consumption	4.2 W max.
Dimensions	45x45x125mm
Weight	260g