

## DIS-2 Multi-D



### Multi decoder with matrix functionality

#### Features

- Drawer module in standard version without hard disks
- Low latency live stream playback (ideal for dome control)
- Simultaneous recording\* and playback of the streams possible (\*only with hard disks)
- Monitor outputs: CVBS (BNC) and S-Video (mini DIN 4)
- Data rate (constant and dynamic): 128 Kbit/sec. – 16 Mbit/sec.
- Video (PAL): up to 720x576 at 25 frames/sec.
- Various video and audio standards can be selected freely
- Other inputs/outputs:
  - 1x 100 Base T x RJ45
  - 1x RS232/RS485 RJ12
  - 1x Audio-OUT 3.5mm phone jack

#### Options

- Max. 2 hard disks
- DIS-2/M component rack

#### Item number

- SL002.DEC

## DIS-2 Multi-D

### Format

Video	MPEG-2 MP@ML MPEG-4 ISO/IEC 14496 H.264
Audio	MPEG-1 Layer 2 ACC

### Video IN / OUT

Video IN	Streaming (LAN)
Video OUT (CVBS)	1 x BNC
Video OUT (S-Video)	1 x mini DIN 4
Video data rate	128 Kbit/Sek. - 16 Mbit/Sek
Decoding time	2ms (1 Fps / D1 resolution)

### Audio IN / OUT

Audio IN	Streaming (LAN)
Audio OUT	1x 3.5 mm phone jack

### Hard disks

Quantity	Max. 2
Type	3,5"
Interface	SATA2

### Interfaces

LAN	1 x RJ45, 10/100 Mbit
Serial	1 x RJ12, RS232 / RS485

### Other hardware details

Mains voltage (incl. admissible tolerance)	12 V DC
Power consumption	max. 25 W
Dimensions	41 x 129 x 553 mm (W x H x D)
Temperature	5° up to 40° C
Humidity	5 up to 70% (not condensing)
Atmospheric load	Dust-free
Weight	approx. 2,5 kg (incl. 2 HDDs)
Operating system	Linux
Languages	German, English, French, Spanish (others on request)